



MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT CODE AND COMPANY INFORMATION

Manufacturer: Tool World Inc.
Emergency Phone: 800.255.3924

Address: P.O. Box 539
300 W. Norton Ave.
Eustis, FL 32726
Information: 352-357-8282
www.twiproducts.com

Product Name:
DURLAST Builders Premium
Product Category:
Latex Primer

Effective Date: June 18, 2004 Rev. 2

SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	OSHA PEL	ACGIH TLV
Ethylene Glycol	107-21-1	50 ppm	39.4 ppm
Texanol	25265-77-4	N/E	N/E
Vinyl Acetate	108-05-4	10 ppm	10 ppm
Amp-95	124-68-5	N/E	N/E
2(Hydroxymethyl) Amino Ethanol	34375-28-5	N/E	N/E

SECTION 3: HAZARD IDENTIFICATION

Hazardous Material Information System (HMIS) Ratings:

1	HEALTH
0	FLAMMABILITY
0	REACTIVITY
E	PROTECTIVE EQUIPMENT

E - Gloves, Respirator, Safety Glasses

0 = Minimal	1 = Slight	2 = Moderate	3 = Serious	4 = Severe
-------------	------------	--------------	-------------	------------

SECTION 4: PHYSICAL DATA

BOILING RANGE: Approx. 200 F
EVAPORATION RATE: Slower than ether
WEIGHT PER GALLON: 11.2 lbs.

VAPOR DENSITY: Lighter than air
% VOLATILE BY VOLUME: 69
V.O.C 0.85 lbs./gal 101.9 g/l

SECTION 5: FIRE AND EXPLOSION DATA

DOT CATEGORY: Not Regulated LEL: N/ E FLASH POINT: >200 F
EXTINGUISHING MEDIA: Water base coating. Will not burn under normal circumstances.
UNUSUAL FIRE OR EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat.
SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to cool containers to prevent pressure build up.

SECTION 6: HEALTH HAZARD / FIRST AID MEASURES

THRESHOLD LIMIT VALUE: Not known.

EFFECTS OF OVEREXPOSURE: *Inhalation* - May cause headache and nausea.

Skin Contact - Possible irritant. (Material is slightly alkaline)

Eye Contact - Primary irritant.

EMERGENCY AND FIRST AID PROCEDURES: *Inhalation* - Remove to fresh air. Seek medical attention.

Skin Contact - Wash effected areas with soap and water. Remove contaminated clothing. Consult a physician.

Eye Contact - Flush immediately with large amounts of water for at least 15 minutes. Take to a physician.

Ingestion - Do not induce vomiting, can cause gastrointestinal irritation.

SECTION 7: REACTIVITY DATA

STABILITY: Unstable____ Stable__X__

CONDITIONS TO AVOID : Excessive heat. Poor ventilation. Materials that react with water.

HAZARDOUS DECOMPOSITION: Thermal decomposition or burning may produce dioxide/carbon monoxide.

HAZARDOUS POLYMERIZATION : Will not occur.

SECTION 8: SPILL OR LEAK PROCUDERS

SPILLED OR RELEASED MATERIAL: Absorb with an inert material, and remove to a disposal container.

WASTE DISPOSAL METHOD: Collect and dispose of in accordance with all local, state, and federal laws.

SECTION 9: SPECIAL PROTECTION INFORMATION

RESPIRATOR PROTECTION: Use NIOSH/MSHA approved cartridge respirator for vapors and mists.

GLOVES: Neoprene gloves for skin protection.

EYE PROTECTION: Use protective goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Protective cream where skin contact is likely.

SECTION 10: SPECIAL PRECAUTIONS

PRECAUTIONS FOR HANDLING AND STORAGE: Keep containers closed when not in use. Do not get in eyes.

OTHER PRECAUTIONS: Prevent prolonged breathing of vapors and mists.

SECTION 11: TRANSPORT INFORMATION

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

SECTION 12: MISCELLANEOUS DATA

The data set forth on this sheet is based on information provided by the suppliers of the raw materials and chemicals used in the production and manufacture of the aforementioned products. TOOL WORLD INC. makes no warranty with respect to the accuracy of the information provided by the suppliers, and disclaims all liability or reliance thereof.

PRODUCT: *Durlast* Builders Premium

DATE: June 18, 2004

PREPARED BY: Alan Semento