



DURLAST

Drywall Primer

Product Category:

Drywall Primers

Product Name:

DURLAST

Product Grade:

Builders Premium

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twidursystem.com



5 Gal Pail



55 Gal Drum
(Items not to scale)



275 Gal Tote

Product Description

DURLAST is a high quality, high solids drywall primer specifically formulated to fill the pores and equalize the suction difference between gypsum board surface paper and compound. *DURLAST* is to be applied as a first coat to the entire, prepared gypsum board surface and skim coatings, to help minimize most decorating problems, prior to decoration.

Advantages

DURLAST is a high hide, fast drying, and economical drywall primer that minimizes joint banding and photographing. *DURLAST* is designed to give you a dry film thickness superior to most high build and paint primers. Due to *DURLAST* excellent hiding properties, it gives you the versatility to apply over trim. *DURLAST* can also act as a texture additive, to increase bond, hide, and whiteness to wall and ceiling spray textures.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be treated with *JOINT BUTTER* as per instructions, must be smooth and dry thoroughly prior to *DURLAST* application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, the sealed with *DS 750 100% Acrylic Primer/Sealer* prior to *DURLAST* application. Prime rust areas with a rust-inhibiting primer. Allow new concrete to cure for 30 days.
3. Painted surfaces should be dulled or apply an appropriate bonding primer prior to *DURLAST* application.

Product Data

MATERIAL: Vinyl Acrylic

COLOR: White or Off White. Can be tinted at store level with most color systems to a variety of pastel or mid-tone colors. (Use up to 4 oz. of universal colorant per five gallons.)

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Mix material thoroughly. If thinning is necessary, do not exceed one pint of clean water per gallon.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Brush, roller, or airless spray machine. (.75 gpm) using .019-.023 tip and 30 mesh filter.

COVERAGE: Approximately 150-300 ft per gallon, depending on surface and equipment.

DECORATION: Dries to touch in 30 minutes under 75° F/50% relative humidity conditions.

NOT INTENDED AS FINAL COAT. SHOULD BE OVERPAINTED WHEN DRY.

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good storage conditions will allow up to 12 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If TWI's *DURLAST* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and a respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273