



# SPRAY-PREP

## Drywall Surfer

**Product Name:**

SPRAY-PREP

**Product Category:**

Drywall Primers

**Manufacturer:**

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ 800.331.8273

☎ 352.357.8282

Fax 352.357.1417

[www.twiproducs.com](http://www.twiproducs.com)



5 Gal Pail



55 Gal Drum



275 Gal Tote

(Items not to scale)

### Product Description

SPRAY-PREP is a high solids drywall surfacer that is specifically formulated to fill the pores and equalize the porosity difference between the gypsum board surface paper and joint compound. SPRAY-PREP is to be applied as a first coat, to the entire prepared gypsum board surface and skim coatings, to help minimize most decorating problems, prior to texturing and/or painting.

### Advantages

SPRAY-PREP is a high hide, fast drying, and economical drywall surfacer that minimizes joint banding and photographing. Because of the solids and superior coverage, a single pass application equals several coats of conventional paint. SPRAY-PREP is designed to achieve a dry film thickness superior to most high build and/or paint primers.

### Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be treated with *JOINT BUTTER* as per instructions, must be smooth and dry thoroughly prior to SPRAY-PREP application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750 100% Acrylic Primer/Sealer* prior to SPRAY-PREP application. Prime rust areas with a rust-inhibiting primer. Allow new concrete to cure for 30 days.

<b>Product Data</b>
---------------------

MATERIAL: Vinyl Acrylic

COLOR: White. Can be tinted at store level with most color systems to a variety of pastel or mid-tone colors. (Use up to 4 oz. of universal colorant per five gallons.)

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Stir material thoroughly.

**DO NOT OVER-THIN PRODUCT.**

APPLICATION: Airless spray machine. (1.25 gpm) using .023-.027 tip and 30 mesh filter.

COVERAGE: Approximately 150-250 ft<sup>2</sup> per gallon, depending on surface and equipment.

DECORATION: Dries to touch in 30-90 minutes under 75° F/50% relative humidity conditions.

**NOT INTENDED AS FINAL COAT. SHOULD BE OVERPAINTED WHEN DRY.**

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good storage conditions will allow up to 12 months shelf life.

**PROTECT FROM FREEZING**

PACKAGING: 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If *SPRAY-PREP* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding wear proper eye protection and a NIOSH approved respirator.

<b>Submittal Approval</b>
---------------------------

Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Approved by: \_\_\_\_\_

Title: \_\_\_\_\_

Date: \_\_\_\_\_

TWI  
300 W. Norton Ave.  
Eustis, FL 32726  
800.331.8273