



CT 900

Interior-Exterior 100% Acrylic Paint

Product Line:
Color Train Paint

Product Name:
CT 900 Interior-Exterior 100% Acrylic Paint

Manufacturer:
Tool World, Inc.
300 W. Norton Ave.
Eustis, FL 32726
☎ (800) 331-8273
☎ (352) 357-8282
FAX (352) 357-1417

Product Description:
Color Train 900 Interior-Exterior, 100% Acrylic Paint is a flat paint which provides a durable, finish coat. An ideal top coat for the Color Train **CT700 & CT750 Primers**.

CT900 can also be applied over drywall, plaster, masonry, and properly prepared wood and metal surfaces.
Packaging: Available in Quarts, Gallons, 5 gallon buckets.
Colors: Available in a wide variety of colors.

Surface Preparation

Previously painted surfaces shall be clean, dry, and free of dust, grease, wax and gloss.

1. Wash surface with water and detergent.
2. After washing, sand glossy areas and rinse.
3. Patch cracks; sand when dry.
4. Let dry completely before applying **CT900**.

Unpainted Plaster, Drywall, and Masonry Surfaces shall be clean, dry, and free of dust, grease, wax, and gloss. Prime with **CT750 or CT700 Primer/Sealer**.

Unpainted Wood Surfaces: Prime with an alkyd primer. Let dry completely before applying **CT900**

Unpainted Metal Surfaces: Prime with a rust inhibiting metal primer. Let dry completely before applying **CT900**.

Application, Equipment:

Apply with nylon or polyester brush, roller, pad, or sprayer (air or airless). Do not apply at room temp. below 50° F. For greater assurance of uniform color, intermix two or more buckets of same color paint. Apply a second coat for additional durability (allow two hours before recoating).

Use a respirator approved by U.S. Bureau of Mines.

Clean tools, equipment, and skin with soapy water and rinse.

Coverage:

Coverage will vary according to surface porosity, and equipment. Average Coverage: 300 sq.ft./gal.

Mixing and Cleaning:

Stir material thoroughly. If thinning is necessary, thin with clean water. Do not exceed 1 pint per gallon.

FORMULA ANALYSIS

PIGMENT:	36%
Titanium Dioxide	40%
Aluminum Silicate	40%
Mica	6%
Diatom. Earth	6%
Mildewcide	8%
Total	100%

PRODUCT DATA:

Type of Pigment:	Titanium Dioxide, Aluminum Silicate
	Mica
	Diatomaceous Earth
	Mildewcide
Type of Vehicle:	Acrylic Resin
Solvent-Thinner:	Water, Ethylene Glycol
Clean-Up:	Water
Packaging:	Quarts, Gallons, 5 gallons
% Solids by Wt.	52.7
% Solids by Vol.	36.3
Pigment Volume	
Conc. (PVC)	48%

7 Year Limited Warranty: If **CT900 Interior Exterior 100% Acrylic Paint** fails to perform as specified, when applied according to label directions, Tool World's obligation shall be limited to refund of purchase price. Sales slip must accompany evidence of failure.

