



# CT 950

## Interior-Exterior 100% Acrylic S/G Enamel

**Product Line:**  
Color Train Paint

**Product Name:**  
CT 950 Interior-Exterior 100% Acrylic S/G

**Manufacturer:**  
Tool World, Inc.  
300 W. Norton Ave.  
Eustis, FL 32726  
☎ (800) 938-7839  
☎ (352) 357-8282  
FAX (352) 357-1417

**Product Description:**  
Color Train 950 Interior-Exterior, 100% Acrylic Paint is a semi-gloss paint which provides a durable, easy to clean finish coat. An ideal top coat for the Color Train **CT700 & CT750 Primers**.

**CT950** can also be applied over drywall, plaster, masonry, and properly prepared wood and metal surfaces.

Packaging: Available in 5 gallon buckets.  
Colors: Available in a wide variety of colors.

### Surface Preparation

Previously painted surfaces shall be clean, dry, and free of dust, grease, wax and gloss.

1. Wash surface with water and detergent.
2. After washing, sand glossy areas and rinse.
3. Patch cracks; sand when dry.
4. Let dry completely before applying **CT950**.

Unpainted Plaster, Drywall, and Masonry Surfaces shall be clean, dry, and free of dust, grease, wax, and gloss. Prime with **CT750 or CT700 Primer/Sealer**.

Unpainted Wood Surfaces: Prime with an alkyd primer. Let dry completely before applying **CT950**

Unpainted Metal Surfaces: Prime with a rust inhibiting metal primer. Let dry completely before applying **CT950**.

### Application, Equipment:

Apply with nylon or polyester brush, roller, pad, or sprayer (air or airless). Do not apply at room temp. below 50° F. For greater assurance of uniform color, intermix two or more buckets of same color paint. Apply a second coat for additional durability (allow two hours before recoating).

**Use a respirator approved by U.S. Bureau of Mines.**

Clean tools, equipment, and skin with soapy water and rinse.

### Coverage:

Coverage will vary according to surface porosity, and equipment. Average Coverage: 300 sq.ft./gal.

### Mixing and Cleaning:

Stir material thoroughly. If thinning is necessary, thin with clean water. Do not exceed 1 pint per gallon.

#### FORMULA ANALYSIS

**PIGMENT:** 36%  
Titanium Dioxide 40%  
Aluminum Silicate 40%

Mildewcide 8%

**Total** 100%

**VEHICLE:** 64%  
Acrylic Resin 40%  
Water 53%  
Wetting Agent 7%  
**Total** 100%

#### PRODUCT DATA:

Type of Pigment: Titanium Dioxide, Aluminum Silicate

Type of Vehicle: Acrylic Resin

Solvent-Thinner: Water, Ethylene Glycol  
Clean-Up: Water

Packaging: Quarts, Gallons, 5 gallons

**% Solids by Wt. 48.5**

**% Solids by Vol. 31.9**

**Pigment Volume**

**Conc. (PVC) 48%**

**7 Year Warranty:** If **CT950 Interior Exterior 100% Acrylic S/G** fails to perform as specified, when applied according to label directions, Tool World's obligation shall be limited to refund of purchase price. Sales slip must accompany evidence of failure.

