



ALL TEX

Non-Aggregated Wall and Ceiling Texture

Product Category:

Drywall Textures

Product Line:

Acusti-Tex

Product Name:

ALL TEX

Manufacturer:

TWI

300 W. Norton Ave.


Eustis, FL 32726

800.331-8273

352.357.8282

Fax 352.357.1417


www.twiproductions.com



All Purpose



Multi-Purpose



Product Description

ALL TEX is an economical, non-aggregated dry powder product formulated to create a variety of textures such as orange peel, knockdown, splatter, skip trowel, stipple, or hand applied textures. *ALL TEX* is designed to hide minor surface imperfections and can be easily applied by hand application or with spray machines, over gypsum wallboard, plaster, and concrete surfaces. *ALL TEX* can be used on walls or ceilings and should be painted when dry. Non contact ceilings can be left unpainted, but if left unpainted, they are not washable.

Advantages

ALL TEX mixes easily, has minimal fallout, and gets excellent mileage. *ALL TEX* provides lower shrinkage than texturing with joint compounds which gives you a higher profile (stand-out) texture.

ALL TEX is available in a variety of formulations:

1. *ALL TEX*- has good open time and is designed for 4-5 man spray crews.
2. *ALL TEX* All Purpose- has better open time and is designed for 3-4 man spray crews.
3. *ALL TEX* Multi-Purpose- has the best open time and is designed for 2-3 man spray crews.

Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss.

1. New gypsum wallboard surfaces and accessories should be primed with *DURLAST* or *SPRAY-PREP* drywall primer prior to *ALL TEX* application.
2. Concrete, plaster, and masonry surfaces must be smooth and cured thoroughly, then sealed with *DS 750* 100% Acrylic Primer/Sealer prior to *ALL TEX* application. Prime rust areas with rust-inhibiting primer. Allow new concrete to cure 30 days.
3. Painted surfaces should be dulled and primed with *DS 750* 100% Acrylic Primer/ Sealer or an appropriate bonding primer prior to *ALL TEX* application.

Product Data

MATERIAL: Dry powder

COLOR: White

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Add enough clean water to produce thick texture. Let stand for approximately 15 minutes, before adding additional clean water to adjust viscosity.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Hopper gun, portable texture machine, airless sprayer (min. 1.25 gpm) with texture atomizer and air compressor (min. 9 cfm), piston or stator type machine.

COVERAGE: Approximately 500-1000 ft² /50 lb. bag. (depending on surface and equipment)

DECORATION: Not intended as final coat. Should be painted when dry.

COMPLIANCE WITH STANDARDS: Meets ASTM E84

STORAGE: Good, dry storage conditions will allow up to 12 months shelf life.

PACKAGING: 50 lb. plastic-lined bags.

WARRANTY: If TWI *ALL TEX* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding, mixing or spraying, wear proper eye protection and respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800.331.8273