



DURSKIM

Acrylic Skim Coating/Texture

Product Category:

Joint Treatments

Product Name:

DURSKIM

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

www.twiproductions.com



5 Gal Pail

Product Description

DURSKIM is a high solids, pre-mixed, interior acrylic compound used for filling or skimming out cinder block, concrete block, brick, and poured or pre-cast concrete to hide joints, cracks, and other minor surface imperfections up to 1/4" deep. *DURSKIM* is designed to provide a dense, uniform surface for painting and texturing. *DURSKIM* is ideal for apartments, hotels, hospitals, manufacturing plants, offices, restaurants, and schools.

Advantages

DURSKIM is a more durable compound, with better adhesion and lower shrinkage than conventional drywall compounds. *DURSKIM* is formulated to provide easy workability and open time for application. It is also more economical than furring and finishing gypsum board. For voids larger than 1/4" it is required to fill voids with *DURSKIM* prior to final application of the product. *DURSKIM* is also an excellent base for Dursystem Texture Coatings, and where high humidity areas such as laundry and pool rooms are of concern.

Surface Preparation

Surfaces shall be clean, sound, dry and free of grease, mildew, dirt, wax, oil, dust, efflorescence, concrete releasing agents, gloss and other contaminants.

1. Prime rust areas with rust-inhibiting primer. Allow new masonry or concrete to cure for at least 30 days.
2. All glossy surfaces must be dulled by lightly sanding. Previously coated surfaces should be free of loose, chalky, cracking, and peeling paint by using a mechanical grinder and/or a pressure washer (min. 2500 psi) with detergent, then rinse thoroughly and allow to dry completely. Determine that all existing coatings are bonded to substrate prior to *DURSKIM* application.

Product Data

MATERIAL: Acrylic type

COLOR: White.

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50°F or above 95°F.

MIXING: Mix thoroughly.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Trowel and/or taping knife.

COVERAGE: Varies on texture of substrate, method of application, surface porosity, waste, and thinning.

DECORATION: Not intended as final coat, should be painted when dry.

STORAGE: Good storage conditions will allow up to 9 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 5 gal. pail

WARRANTY: If *DURSKIM* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and respirator that are NIOSH approved.

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800-331-8273