



JOINT BUTTER®

Ready-Mixed Joint Compound

Product Category:

Joint Treatments

Product Name:

JOINT BUTTER®

Product Grade:

Multi-Purpose

Manufacturer:

TWI

300 W. Norton Ave.

Eustis, FL 32726

800.331.8273

352.357.8282

Fax 352.357.1417

www.twiproductions.com



3.5 gal Carton



4.5 gal Pail

Product Description

JOINT BUTTER® Multi-Purpose is a premixed, ready-to-use, vinyl based joint compound ideal for all phases of gypsum wallboard finishing. JOINT BUTTER® Multi-Purpose can also be used to skim coat, texture, and repair plaster.

Advantages

JOINT BUTTER® Multi-Purpose is formulated to provide superior working qualities such as; up to 30% less shrinkage than conventional joint compounds, excellent adhesion, good crack resistance, excellent sanding qualities, and easy workability. JOINT BUTTER® Multi-Purpose is up to 15% lighter and has superior working qualities compared to regular joint compounds.

Surface Preparation

Surfaces should be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss. Do not apply to shower areas directly exposed to water.

1. Assure that all fasteners and joints are thoroughly dry prior to decorating.
2. New gypsum wallboard surfaces that are to be painted or textured should be primed with TWI's DURLAST drywall primer or SPRAY PLAST® Level 5 Primer/Surfacer.
3. Concrete, plaster, and masonry surfaces must be sealed with DS 750 100% Acrylic Primer/Sealer. Allow new concrete to cure 30 days.

Product Data

MATERIAL: Vinyl type

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50° F or above 95°F.

MIXING: Mix thoroughly. Do not exceed one pint of clean water per 4.5 gallon pail for finishing.

DO NOT OVER-THIN PRODUCT.

APPLICATION: Hand or mechanical

COVERAGE: Approximately 4.5 gallon / 500 ft.² (depending on surface and application)

COMPLIANCE WITH STANDARDS: Meets ASTM C475

STORAGE: Do not store material in direct sunlight, or in temperatures below 32°F.

Good, dry storage conditions will allow up to 9 months shelf life.

PROTECT FROM FREEZING.

PACKAGING: 3.5 gal. carton and 4.5 gal. pail

WARRANTY: If TWI's *JOINT BUTTER* Multi-Purpose fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and respirator

Submittal Approval

Job Name: _____

Job Location: _____

Contractor: _____

Approved by: _____

Title: _____

Date: _____

TWI
300 W. Norton Ave.
Eustis, FL 32726
800.331.8273