



# NUCOAT MH

Drywall Surfer/Finish Primer/Surfer

**Product Category:**

Drywall Primers

**Product Name:**

NUCOAT MH

**Manufacturer:**

TWI

300 W. Norton Ave.

Eustis, FL 32726

☎ (800) 331-8273

☎ (352) 357-8282

Fax (352) 357-1417

[www.twidursystem.com](http://www.twidursystem.com)



5 Gal Pail



55 Gal Drum  
(Items not to scale)



275 Gal Tote

## Product Description

NUCOAT MH is a high quality, high solids drywall coating specifically formulated to fill the pores and equalize the suction difference between gypsum board surface paper and compound.

NUCOAT MH is to be applied to the entire, prepared gypsum board surface, to help minimize most decorating problems, prior to decoration.

## Advantages

NUCOAT MH is a high hide, fast drying, and economical drywall coating that minimizes joint banding and photographing. A single pass application equals several coats of conventional paint. NUCOAT MH is designed to give you a dry film thickness superior to most high build and paint primers.

## Surface Preparation

Surfaces shall be clean, dry, and free of grease, wax, dust, concrete releasing agents, and gloss prior to NUCOAT MH application.

1. New gypsum wallboard surfaces and accessories should be treated with *JOINT COMPOUND* or setting compound as per instructions, must be smooth and dry thoroughly prior to NUCOAT MH application.
2. Prime with vapor barrier when necessary prior to NUCOAT MH application. Vapor barrier paint may be applied over NUCOAT MH when desired.

**Product Data**

MATERIAL: Vinyl Acrylic

COLOR: White. Can be tinted to a variety of pastel or mid-tone colors. (Use up to 4 oz. of universal colorant per five gallons.)

PRODUCT SENSITIVITY: Do not apply when temperatures are below 50° F or above 95° F.

MIXING: Mix material thoroughly.

**DO NOT OVER-THIN PRODUCT.**

APPLICATION: Brush, roller, or airless sprayer. (1.0 gpm) using .021-.025 tip and 30 mesh filter.

COVERAGE: Approximately 150-250 ft<sup>2</sup> per gallon, depending on surface and equipment.

DECORATION: Dries to touch in 30 minutes under 75° F/50% relative humidity conditions.

STORAGE: Good storage conditions will allow up to 12 months shelf life.

**PROTECT FROM FREEZING**

PACKAGING: 5 gallon pail, 55 gallon drum, and 275 gallon tote.

WARRANTY: If TWI's *NUCOAT MH* fails to perform as specified when applied according to specifications, TWI's liability shall be limited to refund of purchase price with proof of purchase.

SAFETY PRECAUTIONS: When dry sanding or spraying, wear eye protection and a respirator that are NIOSH approved.

**Submittal Approval**

Job Name:

\_\_\_\_\_

Job Location:

\_\_\_\_\_

Contractor:

\_\_\_\_\_

Approved by:

\_\_\_\_\_

Title:

\_\_\_\_\_

Date:

\_\_\_\_\_

TWI  
300 W. Norton Ave.  
Eustis, FL 32726  
800-331-8273