

# SPRAY-PREP

## High Build Primer/Surfacers

### PRODUCT DATA

- Resin:** Vinyl Acrylic
- Mixing:** Stir material thoroughly prior to application. Do not thin. May be tinted with universal colorants, up to 2 oz. per gallon.
- Equipment:** Apply with airless sprayer (min 1.25 gpm), pressure at a min. 3000 psi, .021 - .025 spray tip and coarse manifold filter on sprayer (NO filter in gun).
- Coverage:** 145-230 ft<sup>2</sup> /gallon, depending on film thickness, surface, and equipment.
- Decoration:** *TWI Next Level BRAND* SPRAY-PREP is not intended to be used as a final coat and is not, and should not be used as a "sealer". Follow paint manufacturer's specifications for proper surface preparation before final decorations. Apply proper wall sizing, recommended by manufacturer, when applying wallpaper or vinyl wallcovering.
- Application:** Maintain a minimum of 50°F (10°C) product, air, and surface temperature throughout the finishing process until dry including joint compound, primer, and texture products. Apply full coverage coat and let dry. For best results, lightly sand with 180 to 220 mesh screen before final decorations.
- Packaging:** 5 gallon pail, 55 gallon drum, and 275 gallon tote
- Storage:** Store in good storage conditions. Protect from freezing, extreme heat, and direct sunlight.
- Clean Up:** Wipe up drips and spills immediately with wet cloth. Wash tools and exposed skin with clean, soapy water.
- VOC:** <50 g/l

### SURFACE PREPARATION

Surfaces shall be sound, dry, clean, and free from gloss, dirt, dust, grease, mildew, nicotine, concrete releasing agents, and other foreign material. Prime metal with rust-inhibiting primer and age new concrete a minimum of 60 days. Fill and level interior, concrete surfaces with *TWI Next Level BRAND* SLAB-PREP concrete compound or setting-type joint compound. Finish gypsum board, fasteners, and cornerbead with *TWI Next Level BRAND* JOINT-BUTTER joint compound. After completing the finishing process to the adequate level, according to Gypsum Association publication *Recommended Levels of Finish for Gypsum Board* GA-214/ASTM C840, and all surfaces must be completely dry prior to *TWI Next Level BRAND* SPRAY-PREP application.

### SAFETY PRECAUTIONS

Read and understand all safety precautions on SDS before handling material. Avoid breathing spray mist and dust. Use a NIOSH/MSHA approved respirator, and appropriate Personal Protective Equipment in a well-ventilated area.

### NOTICE

TWI warrants its products and goods to the immediate purchaser to be free from defects in material and workmanship at the time of shipment. This warranty is non-assignable and excludes all other warranties including all Implied Warranties of Merchantability and Fitness for a Particular Purpose. TWI shall not be liable for incidental or consequential losses or expenses arising from the sale, handling, or use of their products. Neither shall there be any liability on the part of TWI for loss or damage caused by improper use, storage, or application of their products. Claim must be made in writing no later than 30 days from the date defect was discovered or should have been discovered. If claim is not received within 30 days, claim will be waived. TWI's liability shall be limited to replacement of defective material only.

### SUBMITTAL APPROVALS

<b>Job Name:</b>	
<b>Job Location:</b>	
<b>Contractor:</b>	
<b>Approved By:</b>	<b>Date:</b>

TWI  
300 West Norton Avenue  
Eustis, FL 32726  
800.331.8273  
[www.twiproducs.com](http://www.twiproducs.com)